




INSULATED RING TERMINAL



Terminal material: Copper
Insulation material: Vinyl




ITEM NO.	Stud Size	Width	WIRE SIZE	
	D(mm)	W(mm)	AWG	DIN mm²
RF1.25-3S	3.2	5.5	22-16	0.5-1.0
RF1.25-3	3.7	5.5		
RF1.25-4	4.3	8.0		
RF1.25-4M	4.3	6.6		
RF1.25-5	5.3	8.0		
RF1.25-6	6.4	11.7		
RF1.25-8	8.4	11.7		
RF1.25-10	10.5	13.7		
RF2-3S	3.7	6.5	16-14	1.5-2.5
RF2-3	3.7	6.5		
RF2-4	4.3	8.5		
RF2-4M	4.3	6.6		
RF2-5	5.3	9.5		
RF2-6	6.4	12.0		
RF2-8	8.4	12.0		
RF2-10	10.5	13.7		
RF3.5-4	4.3	8.0	14-12	2.5-4
RF3.5-5	5.3	8.0		
RF3.5-6	6.4	12.0		
RF3.5-8	8.4	15.0		
RF3.5-10	10.5	15.0		
RF5.5-3	3.7	9.4	12-10	4-6
RF5.5-4	4.3	9.5		
RF5.5-5	5.3	9.5		
RF5.5-6	6.4	15.0		
RF5.5-6S	6.4	12.0		
RF5.5-8S	8.4	12.0		
RF5.5-8	8.4	15.0		
RF5.5-10	10.5	15.0		
RF5.5-12	13.0	19.25		
RF8-4	4.3	12.0	8	10
RF8-5S	5.3	9.0		
RF8-5	5.3	12.0		
RF8-6	6.4	12.0		
RF8-8	8.4	15.0		
RF8-10	10.5	15.0		

INSULATED Y TERMINAL



Terminal material: Copper
Insulation material: Vinyl




ITEM NO.	Stud Size	Width	WIRE SIZE	
	D(mm)	W(mm)	AWG	DIN mm²
YF1.25-3S	3.7	5.7	22-16	0.5-1.0
YF1.25-3	3.7	6.2		
YF1.25-4S	4.3	6.4		
YF1.25-4	4.3	7.2		
YF1.25-5	5.3	8.0		
YF1.25-6	6.3	9.7		
YF2-3S	3.7	5.7	16-14	1.5-2.5
YF2-3	3.7	6.2		
YF2-4S	4.3	6.5		
YF2-4	4.3	7.2		
YF2-5	5.3	8.0		
YF2-6	6.4	10.7	14-12	2.4-4
YF3.5-3S	3.7	6.4		
YF3.5-3	3.7	7.4		
YF3.5-4	4.3	8.0		
YF3.5-5	5.3	8.0	12-10	4-6
YF5.5-3S	3.7	7.2		
YF5.5-3	3.7	8.2		
YF5.5-4S	4.3	7.2		
YF5.5-4	4.3	8.2		
YF5.5-5	5.3	9.0		
YF5.5-6	6.4	12.0	8	10
YF8-4	4.3	8.2		
YF8-5	5.3	9.0		
YF8-6	6.4	12.0		

FEMALE LUG COVER



Insulation material: Nylon



ITEM NO.	W	H	L
CLV1-3A	5.2	5.0	20.2
CLV1-5A	7.3	6.1	21.5
CLV1-7A	9.6	6.3	25.2

INSULATED COLOR	
RED:	1.25 mm² = AWG22-16
BLUE:	2.0 mm² = AWG16-14
BLACK:	3.5 mm² = AWG14-12
YELLOW:	5.5 mm² = AWG12-10
WELCOME FOR SPECIAL COLOR REQUEST	

STUD SIZE	
mm - inch	mm - inch
3.2 - #4	6.4 - 1/4"
3.7 - #6	8.4 - 5/16"
4.3 - #8	10.5 - 3/8"
5.3 - #10	13.0 - 1/2"

E	R	F	1.25-3S
Easy Ring entry Type	With Insulated terminal features	Wire range	Stud size

E	Y	F	1.25-3S
Easy Spade entry Type	With Insulated terminal features	Wire range	Stud size