


0801 KSS CLOSE-END WIRE CONNECTOR



- Material : Copper tube with UL94V-2 / V-0 flame rated, UL approved Nylon 66 cover.
- Tested by the glow-wire flammability index (GWFI), at a glow wire temperature of 800°C for UL94V-2 grade and 960°C for UL94V-0 grade.
- Insert pre-stripped wires then use crimping tool to hold wires firmly.



UNIT : mm

Item No.		I.D.	I.D.1	H	H1	Suitable Wires			Packing
UL94V-2	UL94V-0					mm ²	AWG	DIN mm ² d	
CE-1	CE-1V0	7.8	2.4	20.0	7.0	1.25	22-16	0.5-1.75	100pcs
CE-2	CE-2V0	8.0	3.0	20.0	7.0	2.0	16-14	1.0-3.0	
CE-5	CE-5V0	10.5	3.8	25.3	8.0	5.5	12-10	2.5-6.0	
CE-8	CE-8V0	12.0	4.7	27.8	8.5	8.0	8	4.0-9.0	

AWG	2	4	6	8	10	12	14	16	18	20	22	24	26	28	30	32
mm ²	33.4	20.8	13.2	8.4	5.3	3.3	2.1	1.3	0.83	0.52	0.33	0.21	0.13	0.08	0.05	0.03

0804 KSS WIRE NUT DRIVE



- Material : Nylon 66
- Color : Black
- Socket tool used with electronical screwdriver, make fast and easy installation for screw on wire connector.

Item No.	Packing
SWT-1	1 pc



0808 KSS SCREW ON WIRE CONNECTOR



- Material: Steel with UL94V-2 flame rated thermoplastic cover.
- Strip wires before application.
- Rated at 600 volt max. for building wiring.
- Temp. 105°C (221°F)
- Spring design provided more secure connection.

UNIT : mm

Item No.	O.D.	I.D.	H	Wire Combination		Color	Packing
				JIS	AWG		
SW-71BH	8.6	6.5	15.2	Max. 1 #1.25 w/1 #0.75 w/1 #0.5 Min. 2 #0.5	Max. 1 #16 w/1 #18 w/1 #20 Min. 2 #22	Grey	100pcs
SW-72BH	9.9	7.1	17.7	Max. 3 #1.25 Min. 2 #0.5	Max. 3 #16 Min. 2 #22	Blue	
SW-73BH	12.7	9.7	22.0	Max. 4 #1.25 w/1 #0.5 Min. 1 #0.75 w/1 #0.5	Max. 4 #16 w/1 #20 Min. 1 #18 w/1 #20	Orange	
SW-74BH	14.0	11.0	24.6	Max. 2 #3.5 w/2 #2.0 Min. 3 #0.5 Sol	Max. 2 #12 w/2 #14 Min. 3 #20 Sol	Yellow	
SW-76BH	16.3	13.1	26.5	Max. 2 #5.5 Sol w/2 #3.5 Str Min. 3 #0.75	Max. 2 #10 Sol w/2 #12 Str Min. 3 #18	Red	

