

DUAL-SIDE ENTRY, STACKED DOUBLE ROW

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
IPLDS350-4	350 - 10	4	2.50	3.91	3.75	514-657	5/16
IPLDS350-6		6	3.55	3.91	3.75	770-985	5/16
IPLDS350-8		8	4.60	3.91	3.75	1028-1314	5/16
IPLDS350-10		10	5.65	3.91	3.75	1028-1314	5/16
IPLDS350-12		12	6.70	3.91	3.75	1028-1314	5/16
IPLDS500-4	500 - 4	4	2.90	4.71	4.30	631-806	5/16
IPLDS500-6		6	4.01	4.71	4.30	946-1209	5/16
IPLDS500-8		8	5.16	4.71	4.30	1262-1612	5/16
IPLDS500-10		10	6.30	4.71	4.30	1262-1612	5/16
IPLDS500-12		12	7.45	4.71	4.30	1262-1612	5/16
IPLDS500-14		14	8.59	4.71	4.30	1262-1612	5/16
IPLDS500-16		16	9.74	4.71	4.30	1262-1612	5/16
IPLDS600-4	600 - 6	4	3.37	4.71	4.30	810-1035	5/16
IPLDS600-6		6	4.47	4.71	4.30	1215-1554	5/16
IPLDS600-8		8	5.77	4.71	4.30	1262-1612	5/16
IPLDS600-10		10	7.07	4.71	4.30	1262-1612	5/16
IPLDS600-12		12	8.37	4.71	4.30	1262-1612	5/16
IPLDS600-14		14	9.67	4.71	4.30	1262-1612	5/16
IPLDS600-16		16	10.97	4.71	4.30	1262-1612	5/16
IPLDS600-20		20	13.57	4.71	4.30	1262-1612	5/16
IPLDS750-6*	750 - 1/0	6	4.90	4.97	4.96	1395-1767	3/8
IPLDS750-8*		8	6.33	4.97	4.96	1860-2356	3/8
IPLDS750-10*		10	7.75	4.97	4.96	1860-2356	3/8
IPLDS750-12*		12	9.18	4.97	4.96	1860-2356	3/8
IPLDS750-16		16	9.18	4.71	4.3	1860-2356	3/8
IPLDS750-20		20	9.18	4.71	4.3	1860-2356	3/8
IPLDS7502-1/010**	750 - 1/0	2	6.460	4.470	3.39	1860-2356	3/8
	1/0 - 14	10					3/16

IN-LINE ENTRY

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
ISR-4	4 - 14 AWG	2	2.26	0.80	1.38	75-95	1/8
ISR-2	2 - 14 AWG	2	2.26	0.80	1.35	100 - 130	5/32
ISR-1/0	1/0 - 14 AWG	2	3.25	0.90	1.48	280-350	3/16
ISR-2/0	2/0 - 14 AWG	2	3.25	0.90	1.48	150-195	3/16
ISR-3/0	3/0 - 6 AWG	2	3.50	0.95	1.75	175-225	1/4
ISR-250	250 MCM - 6 AWG	2	4.00	1.19	1.90	435*535	5/16
ISR-350	350 MCM - 10 AWG	2	4.47	1.32	2.20	135-170	5/16
ISR-500	500 MCM - 4 AWG	2	4.62	1.62	3.00	230-290	5/16
ISR-600	600 MCM - 6 AWG	2	5.83	1.75	3.30	280-350	5/16
ISRH-750	750 MCM - 1/0 AWG	2	7.25	1.75	3.50	350-430	5/16

MOUNTABLE, SINGLE-SIDE ENTRY

CATALOG NUMBER	WIRE RANGE (Kcmil/AWG)	PORTS	LENGTH (IN.)	WIDTH (IN.)	HEIGHT (IN.)	MAX AMP (ALUM-COPP)	HEX KEY (IN.)
IPLM4-4	4 - 14	4	3.26	1.24	1.47	75-95	1/8
IPLM1/0-4	1/0 - 14	4	4.19	1.55	1.84	135-170	3/16
IPLM1/0-5		5	4.84	1.55	1.84	135-170	3/16