



Representative Image

Catalog No. TL12412C**Description: MAIN LUG 125A 12CRT COMBO LD CENTER****UPC No 783164189889****Home > Load Centers > Load Centers**

Main lug load centers can be used as a home's main panel or sub panel depending upon your preferences. All ABB load centers are rated up to 60 degree/75 degree centigrade and is suitable for use with service entrance equipment when installed in accordance with electrical code. The TL12412C features space for 12, 1" breakers, 3 phases, a 125 A bus ampere rating, and a combination surface/flush enclosure.

Descriptors

Category	Load Centers
GO Schedule	R7

Specifications

# Branch Circuit 250A	12
1" Space	12
1/2" Space	0
Amperage	125 A
Circuit Breaker Style	Plug-In
Device type	Main Lug
Door	Yes
Enclosure	Indoor
Enclosure Type	Indoor, Combination
Factory Installed Ground Kit	No
Feed	Either
Input/Output Voltage	208Y/120V ac
Interrupting Capacity Rating	65
Load Center Type	Standard
NEMA Rating	NEMA 1
Phase	3 Phase
Service & Voltage	3 Phase, 4 Wire, 208Y/120V ac
Wires	4 Wire

Classifications

UL/CUL Listing	UL
----------------	----

Dimensions

Depth	3.7 in
Height	19.0 in
Weight	18.8 lb

by ABB

Dimensions

Width	14.0 in
-------	---------

Publications

Title	Publication No.	Publication Type
Section 1 BuyLog: Load centers, meter combos, single socket metering, and residential circuit breakers Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line.	DET1023	Application and Technical

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.