



Pass and Seymour  
Straight Blade CONN 3W 15A 250V HG PS5669XHG  
Part No. PS5669XHG

Straight Blade Connector 2-Pole 3-Wire 15A 250V Hospital Grade



## Features & Benefits

Unit arrives completely ready-to-wire, cuts installation time significantly.

Nylon housing provides impact and chemical resistance.

Rugged two-piece cord grip provides more uniform cord retention.

Internal dust shield keeps terminals free of contaminants.

Tri-drive assembly screws are standard on Hospital Grade plugs and connectors (angle plugs not included).

All 3-wire terminals located on the same plane, allows for quick wire termination from any angle.

Heavy-duty brass alloy blades and contacts, resist heat rise, provide excellent conductivity.

Cord-grip screws recessed to protect installer against screwdriver head slippage.

For covering patents, see [www.legrand.us/patents](http://www.legrand.us/patents).

## Specifications

### General Info

|                    |                         |                   |                |
|--------------------|-------------------------|-------------------|----------------|
| Product Line       | Pass & Seymour          | Color             | Black          |
| UPC Number         | 785007236866            | Country Of Origin | Mexico         |
| Application Sector | Commercial, Residential | Standard          | UL498, FEDSPEC |

### Dimensions

|                  |          |                   |          |
|------------------|----------|-------------------|----------|
| Product Width US | 1.358 in | Product Length US | 2.638 in |
|------------------|----------|-------------------|----------|

### Listing Agencies / 3rd Party Agencies

|              |     |
|--------------|-----|
| cULus Listed | Yes |
|--------------|-----|

Additional Information

|                               |     |
|-------------------------------|-----|
| Product Environmental Profile | Yes |
|-------------------------------|-----|

Technical Information

|           |             |                 |             |
|-----------|-------------|-----------------|-------------|
| Phase     | Three       | Number of Wires | 3           |
| Amperage  | 15 A        | Number of Poles | Double Pole |
| Wire Size | 18 - 12 AWG | Voltage         | 250.0 V     |