

Specifications



Photo is representative



Eaton C25END425B

Eaton definite purpose contactor, Non-reversing contactors and starters (C306) , 25–40A, four-pole , Open with metal mounting plate, Screw/pressure plate and quick connect terminals (side-by-side), 4P,25A, 208–240 Vac, 50/60 Hz

General specifications

PRODUCT NAME	Eaton definite purpose contactor
CATALOG NUMBER	C25END425B
UPC	782113554068
PRODUCT LENGTH/DEPTH	3.38 in
PRODUCT HEIGHT	3.5 in
PRODUCT WIDTH	2.68 in
PRODUCT WEIGHT	2.05 lb
WARRANTY	1 year
COMPLIANCES	RoHS Compliant
CERTIFICATIONS	CSA Certified UL Recognized
CATALOG NOTES	Resistive Load rating per pole

Product specifications

AMPERAGE RATING	25A
NUMBER OF POLES	Four-pole
TYPE	Non-reversing
COIL	208-240 Vac, 50/60 Hz
ENCLOSURE	Open with metal mounting plate
FRAME SIZE	15-50 A, two-pole and three-pole
INDUCTIVE FULL LOAD	25 A
MODEL	Contactator
RESISTIVE LOAD	35 A
TERMINALS	Screw/pressure plate and quick connect terminals (side-by-side)
CONNECTION	Quick

Resources

CATALOGS	Motor Control and Protection, Definite Purpose Contactors and Starters, Volume 5, Tab 4
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - C25END425B

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.