

Click below to order

Interlight Specialty Bulbs
1-800-743-0005
www.interlight.biz



Incandescent Lamps

Shape	Base	Order Watts	Code	Description	Volts	Case Qty.	Filament Design	MOL	LCL	Rated Life Hours	Lumens Initial	Color Temp. K	CBCP	Beam Spread	Footnotes	Additional Information
INCANDESCENT LAMPS (CONTINUED)																
55 WATTS																
A19	Med	55	11904	55A/SW/MI 48PK	120	144	CC-8	4.43	3.12	1000	800					Soft White, Miser®
60 WATTS																
A15	Med	60	14029	60A15/W/CF-CD2	120	60	C-9	3.5	2.37	1500	650					White, Ceiling-Fan, Vibration-Resistant
			17759	60A15/CF CD2	120	60	C-9	3.5	2.37	1500	650					Clear-Ceiling Fan and Appliance, Vibration Resistant
			46888	60A15CF/STGPQ2/6	120	30	C-9	3.5	2.37	1500	650					Ceiling Fan Saf-T-Gard®
			48698	60A15/CF/RVL CD2	120	30	C-9	3.5	2.375	1500	480					Reveal® Clear-Ceiling Fan. Vibration Resistant
A19	Med	60	14052	60A/SSW-24PK	120	120	CC-8	4.43	3.12	1000	840					Super Soft - Soft White
			14414	60A/CVG 24PK	120	24	CC-6	4.43	3.12	1000	850					Inside Frost-covRguard®, Teflon® Coated
			16364	60A/BLB-CD	120	24	C-9	4.43		1000						Black Light; Carded
			20326	60A/SPK 24PK	120	120	CC-6	4.43	3.12	1000	675					Soft Pink
			22361	60A/COMM 24PK	120	24	CC-6	4.43	3.12	1000	855					Inside Frost
			22384	60A/GD 24PK	120	24	C-9	4.43	3.12	3000	635					Light I.F.-Garage Door, Vibration Resistant
			23097	60A/GD CD	120	24	C-9	4.43	3.12	3000	635					Light I.F. Garage Door, Vibration Resistant, Carded
			25905	60A/BLB 6PK	120	30	C-9	4.43		1000				2A, 2F, 5B, 7A, 7C, 9K		Black Light
			39322	60A/CL 24PK	120	120	CC-6	4.43	3.12	1000	870					Clear
			40324	60A/S-120V-24PK	120	24	C-9	4.43	3.12	3000	600					Survivor™ LongLife I.F., Vibration Resistant, BB
			41026	60A 48PK	120	144	CC-6	4.43	3.12	1000	865					Standard
			41028	60A/W 48PK	120	144	CC-6	4.43	3.12	1000	840					Soft White
			41284	60A/Y 24PK	120	120	CC-6	4.43	3.12	1000	550					Yellow Bug-Lite
			41285	60A/W/LL 24PK	120	120	CC-6	4.43	3.12	1500	820					Soft White-LongLife
			41624	60A/PL 6PK	120	30	CC-6	4.43	3.12	1000	630			5E		Plant Light
			46845	60A/W/STG PQ2/10	120	100	CC-6	4.43	3.12	1000	812					Soft White Saf-T-Gard®
			48688	60A/RVL 48PK	120	144	CC-8	4.43	3.12	1000	630					Reveal® Soft White
			81639	60A/CL/RVL 24PK	120	120	CC-6	4.43	3.12	1000	650					Reveal® Clear
		60	16783	60A	130	120	CC-6	4.43	3.12	1000	850					Inside Frost
		53			120					2600	640					(Ratings @ 120 volts.)
		60	40325	60A/S-130V-24PK	130	24	C-9	4.43	3.12	3000	600					Survivor™ LongLife I.F., Vibration Resistant, BB (Ratings @ 120 volts.)
		53			120					8300	460					
A21	Med	60	17122	60A21	230	120	C-17A	4.37	2.75	1000	585					Inside Frost
			16997	60A21/B	120	120	C-9	4.87		1000				2B		Blue
			17027	60A21/R	120	120	C-9	4.87		1000				2B		Red
			17968	69A21/60WM/TS		120	C-11V	4.37	2.43	8000	610					Watt-Miser®-Clear, Traffic Signal, Burn BDTH, BB
			17969	69A21/60WM/TS		120	C-11V	4.37	2.43	8000	610					Watt-Miser®-Clear, Traffic Signal, Burn BDTH, BB
R46	Scrw Term	60	17212	60PAR/2/R	38	12	CC-2V	3.75		800						Red Lens-Train Warning
T8	Disc	60	17226	L60	120	24	C-8	17.75		1500	480					Clear-Lumiline
			17266	L60/W	120	12	C-8	17.75		1500	450					White-Lumiline
T10	Med	60	17292	60T10/64 24PK	120	192	C-8	5.62		1000	740					Clear-Showcase, BDTH
65 WATTS																
BR30	Med	65	18011	65R/FL/MI/TWIN	120	6	CC-6	5.37		2000	755			2A, 5E, 9K		Reflector Flood Twin Pack
			20331	65R/FL/MI/1 6PK	120	30	CC-6	5.37		2000	755			2A, 5E, 9K		Reflector Flood
			20332	65R/SP/MI/1 6PK	120	30	CC-6	5.37		2000	755			2A, 5E, 9K		Reflector
			20996	65R30/PL/1 6PK	120	30	CC-6	5.37		2000				2A, 5E, 9K		Reflector -Plant Light, BB
			22714	65R30/FL/COMM 12PK	120	12	CC-6	5.37		2000	755			2A, 5E, 9K		Reflector Flood 12 Pack
			26641	65R30/FL/B	120	30	CC-6	5.37		2000				2A, 5E, 9K		Reflector - Blue