

Product data sheet

Characteristics

NF442L4C

NF Pnlbrd Interior 400A, 3 PH, 4 Wire, 42 CCT,
Mn Lug, Cu



Product availability: Stock - Normally stocked in distribution facility



Main

Load center type	Main lugs
Circuit breaker type	EDB/EDG/EDJ
Material	Copper

Complementary

Number of spaces	42
Enclosure nominal height	56 in 68 in
Enclosure nominal width	20 in
Enclosure nominal depth	5.75 inFor NEMA 1 enclosure 6.5 inFor NEMA 3R/5/12 enclosure
Line Rated Current	400 A
Wiring configuration	4-wire
Phase	3 phases
System Voltage	480Y/277 V AC


Environment

Standards	CSA C22.2 UL 67
-----------	--------------------

Ordering and shipping details

Category	08350 - NF MLO INTERIOR RTA
Discount Schedule	PE1A
GTIN	00785901871613
Nbr. of units in pkg.	1
Package weight(Lbs)	31.18
Returnability	Y
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1419 - Schneider Electric declaration of conformity  Schneider-Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------

Product Life Status :	Commercialised
-----------------------	----------------