

Wiha Insulated Ratcheting Cable Cutters

Insulation: VDE, EN/IEC, ASTM, NFPA70E, CSA & OSHA Tested to 10,000 volts with



\triangle 1000volt

11980 Insulated ACSR Ratcheting Cable

Cutter Replaceable tool steel cutting blades are securely mounted for accurate cutting. Handles lock in closed position for easier storage. High leverage ratchet mechanism for best cutting performance. 13.9" OAL

Item	OAL	up to	Inch		-	
No.	mm	MCM	Dia.	Capacity	lbs.	Pkg.
11980	353	477	1.25"	32ml	3.4	1



119 High Voltage Double-Insulated Ratcheting Cable Cutters

High leverage ratchet cable cutter with shear type blades cuts stranded & flexible copper and aluminum cable. Not for use on steel. Features built in safety release in all cutting positions, and high-visibility comfort grip handles.

Item	OAL		up to	Inch	
No.	mm/Inch	MCM	Dia.	Сар.	lbs. Pkg.
11960	250/10.0"	500	1.25"	32ml	1.58 1
11975	280/11.0"	750	2.0"	52ml	2.02 1

Insulated Stripping Pliers



1000volt

10250 Insulated Stripping Pliers.
Insulation According to EN/IEC 60900,
DIN ISO 8976, ASTM F-1505 & CSA
Specification. Individually Tested.

Wide long head with ridged gripping surface, shears blade and firm wire stripping stations. Wire stripping stations 0.81 / 1.0 / 1.3 / 1.6 / 2.0 / 2.59mm, AWG 20 / 18 / 16 / 14 / 12 / 10.

Item No. mm Inch Ø AWG lbs. Pkg. **10250** 160 6.3" 0.81-2.59 20-10 .26 1

Insulated End Cutters



End Cutters, With Insulated
Handle. Insulation According to EN/IEC
60900, DIN ISO 8976, ASTM F-1505 & CSA
Specification. Individually Tested. Blade
alloyed tool steel. Induction hardened.

Item	OAL	OAL	Cap.	
No.	mm	Inch	Inch	lbs. pkg.
29250	250	10.0"	7/8"	1.1 1

Insulated Pliers Wrench



Handle Insulation According to EN/IEC 60900, DIN ISO 8976, ASTM F-1505 & CSA Specification, Up To 1000 Volt. Individually Tested. Chrome-vanadium steel, drop forged, oil hardened.

Item	OAL	OAL	•	
No.	mm	Inch	lbs.	pkg.
11610	254	10.0"	1.67	1

Proturn Insulated Electrician's Shears



32951 Proturn Insulated Electrician's Shears Insulation meets VDE, ASTM, EN/IEC, CSA, NFPA OSHA Specifications.

Made from stainless 420 grade steel

Item				← →	
No.	mm	Inch	Pkg.	lbs.	
32951	160	6.3	1	.22	

Wiha Insulated Adjustable Wrenches



∕≺1000volt

Insulated 8" Adjustable Wrench
Insulation According to ASTM, EN/IEC,
NFPA, CSA and ISO Specification, up to
1000 Volt. Individually Tested. Etched on
scale for pre-setting size. Slip guard handle for
added protection.

Item	OAL	OAL	Capacity	<u></u>	
No.	Inch	mm	Opening	lbs.	pkg.
76208	8.0	200	1"	7	1

76210	Insulated 10" Adjustable Wrench						
Item	OAL	OAL	Capacity	- →			
No.	Inch	mm	Opening	lbs.	Pkg.		
76210	10.0	250	1-1/4"	1.4	1		

76212 Insulated 12" Adjustable Wrench						
Item	OAL	OAL	Capacity	-		
No.	Inch	mm	Opening	lbs.	Pkg.	
76212	12.0	300	1-1/2"	1.9	1	

$hinspace \pm 1000 \text{volt}$

76215	Insulated 15" Adjustable Wrench						
Item	OAL	OAL	Capacity	•			
No.	Inch	mm	Opening	lbs.	Pkg.		
76215	15.0	380	1-11/16"	2.8	1		



76290 3 Pc. Insulated Adjustable

Wrenches Etched on scale for pre-setting size. Slip guard handle for added protection.

Item No. 76290 Includes the following:

lbs. 4.0 8.0", 10.0", 12.0" Adj. Pliers