

#### Wiha Canvas Pliers Holster


- · Canvas holster with belt clip and belt loop
- · Security pliers strap
- · Screwdriver holder in the front

91256	Pliers Canvas Holster						
Item	Width	Height	•••				
No.	Size	Size	lbs.	pkg.			
91256	3.5 x	6.75	.15	1			





# Wiha Inomic 1000Volt Insulated Pliers





Inomic Combo Pliers. Insulation According to EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, Qup to 1000 volt.

Individually Tested. DIN ISO 5749 Precision machined forged head. Induction hardened for longest tool life. Cross hatched flat jaw & deep cut radius jaws for secure gripping of the work piece. Cutting edges are matched for precise cutting action. Award winning ergonomic design with head mounted at 23° angle to grip for reduced user fatigue. Palm side of grip has molded soft panel for added comfort in prolonged use.

0 1		•			0
Item	↔	<b>→</b>	<b>Cutting Capacity</b>		<del></del>
No.	mm	Inch	Copper AWG	Pkg.	lbs.
32850	180	7.0	#6	1	.46
32852	Inomic Long No	se Plie	rs		
Item	→	<b>←→</b>	<b>Cutting Capacity</b>		•••
No.	mm	Inch	Copper AWG	Pkg.	lbs.
32852	160	6.3	#6	1	.43
32854	Inomic Diagonal	Cutter	's		
Item	→	$\leftarrow$	<b>Cutting Capacity</b>		<del></del>
No.	mm	Inch	Copper AWG	Pkg.	lbs.
32854	160	6.3	#6	1	.41

Tools Meet 10,000 Volt Test Standards Rated to 1000Volt ac or 1500 Volt dc



91230	Inomic Canvas Holster							
Item	Width	Height	<b>-</b> →					
No.	Size	Size	lbs.	pkg.				
91230	4.0 x	4.5	.05	1				

## **Proturn Insulated Electrician's Shears**



32951 Proturn Insulated Electrician's Shears
Insulation meets VDE, ASTM F1505, EN/IEC 60900, CSA, NFPA
70E. OSHA Specifications. Made from stainless 420 grade steel

Item				***
No.	mm	Inch	Pkg.	lbs.
32951	160	6.3	1	.22

#### **Insulated Water Pump Pliers**



**☆1000volt** 

Insulated Industrial Water Pump Pliers. Insulation
According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505,
NFPA70E and CSA, up to 1000 Volt. Individually Tested.

10 opening settings provides optimal adjustment to objects being gripped. Long life achieved through additional induction hardening of jaws to approx. 62HRC. Chrome-vanadium tool steel forgings, hardened and tempered. Black finish.

Item	<b>←→</b>	<b>→</b>	Capacities			•••
No.	mm	Inch	Round	Hex	Pkg.	wt.
32954	250	10.0	1 3/4	2	1	.90

## **Insulated Push Button Water Pump Pliers**



Insulated Industrial Push Button Water Pump Pliers.
Insulation According to VDE 0682/part 201, EN/IEC 60900, ASTM F-1505, NFPA70E and CSA, up to 1000 Volt. Individually
Tested. Extra narrow head for working in small spaces. Rapid and simple push button setting & locking. Long life achieved through additional induction hardening of jaws to approx. 62HRC. Finger jam protection for safe operation at all settings. CVM tool steel forgings, hardened & tempered.

Item	$\leftarrow$	<b>→</b>	Capacities			•••
No.	mm	Inch	Round	Hex	Pkg.	wt.
32956	250	10.0	1 3/4	2"	1	.90