

## Wiha Insulated Screwdrivers with SoftFinish® Cushion Grip Handle

### Insulation Test Standards:

Insulation according to EN/IEC 60900, ASTM F-1505, New VDE 0682/part 201, DIN 7437, NFPA70E & CSA

Responds to OSHA's use specification 29 CFR1910

Each tool individually tested to 10,000 volts and rated to 1000 Volt ac or 1500 Volt dc

**SoftFinish® handle** Solid molded core with soft outer cushion grip. 40% more torque than conventional handles

### Insulation

Molded directly onto the blade for permanent bonding

### Blade

CVM tool steel, hardened to average 58/60RC

**1000V**



**1000Volt**



**320** Slotted Screwdriver, With Wiha-SoftFinish® Handle. Insulation According to ASTM F-1505, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, up to 1000 Volt. Individually Tested.

| Item No. | mm   | Inch | Inch  | mm  | Inch | mm  | Inch | lbs. | pkg. |
|----------|------|------|-------|-----|------|-----|------|------|------|
| 32005    | 2.0  | .078 | 5/64  | 60  | 3.0  | 164 | 6.5  | .05  | 10   |
| 32010    | 2.5  | .098 | 3/32  | 75  | 3.0  | 179 | 7.1  | .06  | 10   |
| 32012    | 3.0  | .118 | 1/8   | 100 | 4.0  | 204 | 8.0  | .07  | 10   |
| 32015    | 3.5  | .139 | 9/64  | 100 | 4.0  | 204 | 8.0  | .07  | 10   |
| 32017    | 4.0  | .157 | 5/32  | 100 | 4.0  | 211 | 8.3  | .12  | 10   |
| 32023    | 4.5  | .177 | 3/16  | 100 | 4.0  | 211 | 8.3  | .12  | 10   |
| 32024    | 4.5  | .177 | 3/16  | 125 | 5.0  | 236 | 9.3  | .12  | 10   |
| 32027    | 4.5  | .177 | 3/16  | 150 | 6.0  | 261 | 10.2 | .14  | 10   |
| 32025    | 4.5  | .177 | 3/16  | 175 | 7.0  | 286 | 11.2 | .13  | 10   |
| 32028    | 4.5  | .177 | 3/16  | 200 | 8.0  | 311 | 12.3 | .15  | 10   |
| 32031    | 5.5  | .216 | 7/32  | 125 | 5.0  | 243 | 9.5  | .15  | 10   |
| 32026    | 5.5  | .216 | 7/32  | 175 | 7.0  | 293 | 11.5 | .21  | 10   |
| 32034    | 6.0  | .236 | 15/64 | 150 | 6.0  | 268 | 10.6 | .21  | 10   |
| 32039    | 6.5  | .255 | 1/4   | 150 | 6.0  | 268 | 10.6 | .21  | 10   |
| 32042    | 8.0  | .315 | 5/16  | 175 | 7.0  | 299 | 11.8 | .34  | 10   |
| 32045    | 10.0 | .393 | 3/8   | 200 | 8.0  | 318 | 12.5 | .39  | 10   |



**1000Volt**

**32105** 2 Piece Slotted & Phillips Set

Item **Slotted: 5.5**

No. **Phillips: #2**

32105 **lbs. .50**



**1000Volt**

**33532** 2 Piece Slotted & Phillips Set

Item **Slotted: 6.0**

No. **Phillips: #2**

33532 **lbs. .50**

**1000Volt**



**321** Phillips Screwdriver, With Wiha-SoftFinish® Handle. Insulation According to ASTM F-1505, New VDE Specification 0682/part 201 and EN/IEC 60900, NFPA70E & CSA, up to 1000 Volt. Individually Tested.

| Item No. | Size | mm  | Inch | mm  | Inch | lbs. | pkg. |
|----------|------|-----|------|-----|------|------|------|
| 32100    | 0    | 60  | 2.4  | 164 | 6.5  | .06  | 10   |
| 32101    | 1    | 80  | 3.0  | 191 | 7.5  | .12  | 10   |
| 32102    | 2    | 100 | 4.0  | 218 | 8.6  | .20  | 10   |
| 32103    | 3    | 150 | 6.0  | 268 | 10.6 | .34  | 10   |
| 32104    | 4    | 200 | 8.0  | 318 | 12.5 | .39  | 10   |

**1000Volt**



**1000Volt**

**32090** 4 Piece Slotted & Phillips Set

Item No. **Slotted: 3.5, 4.5**

32090 **Phillips: #1, 2**

**lbs. .76**