


Downlight LED Redondos



Dimensiones		
	B	C
3W	20mm	Ø83mm
6W	20mm	Ø118mm
12W	20mm	Ø168mm
15W	20mm	Ø188mm
18W	20mm	Ø220mm
24W	20mm	Ø293mm

Código	Modelo	Tensión	Potencia	Temperatura de Color	Flujo Luminoso	Código de Barras	Caja
95053	EMPOTRAR REDONDO	100-277V	3W	3.000K	135lm	4897082827689	60 unid.
95600	EMPOTRAR REDONDO	100-277V	3W	4.000K	135lm	4897082827740	60 unid.
95059	EMPOTRAR REDONDO	100-277V	3W	6.000K	135lm	4897082827801	60 unid.
95054	EMPOTRAR REDONDO	100-277V	6W	3.000K	300lm	4897082827696	60 unid.
95601	EMPOTRAR REDONDO	100-277V	6W	4.000K	300lm	4897082827757	60 unid.
95060	EMPOTRAR REDONDO	100-277V	6W	6.000K	300lm	4897082827818	60 unid.
95055	EMPOTRAR REDONDO	100-277V	12W	3.000K	730lm	4897082827702	30 unid.
95602	EMPOTRAR REDONDO	100-277V	12W	4.000K	730lm	4897082827764	30 unid.
95061	EMPOTRAR REDONDO	100-277V	12W	6.000K	730lm	4897082827825	30 unid.
95056	EMPOTRAR REDONDO	100-277V	15W	3.000K	1.000lm	4897082827719	30 unid.
95603	EMPOTRAR REDONDO	100-277V	15W	4.000K	1.000lm	4897082827771	30 unid.
95062	EMPOTRAR REDONDO	100-277V	15W	6.000K	1.000lm	4897082827832	30 unid.
95057	EMPOTRAR REDONDO	100-277V	18W	3.000K	1.200lm	4897082827726	20 unid.
95604	EMPOTRAR REDONDO	100-277V	18W	4.000K	1.200lm	4897082827788	20 unid.
95063	EMPOTRAR REDONDO	100-277V	18W	6.000K	1.200lm	4897082827849	20 unid.
95058	EMPOTRAR REDONDO	100-277V	24W	3.000K	1.600lm	4897082827733	20 unid.
95605	EMPOTRAR REDONDO	100-277V	24W	4.000K	1.600lm	4897082827795	20 unid.
95064	EMPOTRAR REDONDO	100-277V	24W	6.000K	1.600lm	4897082827856	20 unid.



VIDA ÚTIL (L70)
25.000h



ÁNGULO DE
APERTURA 110°



GRADO DE PROTECCIÓN
IP20*

