



Color :

Black-White

**UPC Code:** 078477807989

Country Of Origin: Mexico

**NEMA:** 

L5-30P

#### **Available Colors:**





Yellow-White

# 2611

Locking Plug, 30 Amp, 125 Volt, Industrial Grade, Black & White

30 Amp, 125 Volt, NEMA L5-30P, 2P, 3W, Locking Plug, Industrial Grade, Grounding - Black/White

**ROHS Compliant:** Yes

Leviton's Black & White line of industrial grade plugs, connectors, flanged inlets, and outlets offer superior performance, long lasting reliability and features that are backed by a limited lifetime warranty:

- One piece contacts reduce friction and overheating
- Unique cord clamp accepts wide range of cord sizes (.245"-.700")
- Rugged nylon construction resists impact, sunlight, chemicals, and rough use
- Industry exclusive limited lifetime warranty
- Ideal for generators and camper trailers

### **Technical Information**

**Electrical Specifications** 

Amperage: 30 A

**Current Interrupting:** Certified for current interrupting at full rated current

**Dielectric Voltage:** Withstands 2000V per UL498

**Grounding:** Grounding

Pole: 2

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 125 VAC

Wire: 3

Material Specifications

Assembly Screws: Steel, Zinc At Rated Voltage: 2 HP

Plated

**Back Cover:** Thermoplastic

Blades/Contacts: Solid Brass

**Body Material:** Impact

Modified Nylon

Clamp Insert: Nylon

Color: Black-White

Cord-Clamp: Nylon

**Environmental Specifications** 

**Environment**: Dry

Flammability: Rated V-2 per

**UL 94** 

**Operating Temperature: -40°** 

C to 60°C

Mechanical Specifications

Cord Range: 0.520 to 0.930

Product ID: Ratings are permanently marked on device

Terminal Accom.: 18-10 AWG

Terminal ID: Brass-Hot. Green-Ground, Silver-Neutral

Torque Range: 10-14 in-lbs

Wire Gauge: 16-8 AWG

Terminal Screws: Brass

Wire Module: Nylon

Product Features Standards and Certifications

**Brand**: Black and White **ANSI**: C-73

Color : Black-White CSA C22.2 No. 42 : File LR-406

**Device Type :** Locking Plug **NEMA :** WD-6

**NEMA**: L5-30P **NOM**: 057

UL Fed Spec WC-596: File


E13393

UL498: File E13393

Warranty: Limited Lifetime

Warranty Warranty

## **Dimensional Drawing**



## Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S. T. Monday-Friday): +1-800-824-3005

## Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 · FAX: +1-800-824-3005 ·

## Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 ·

## Visit our Website at: www.leviton.com

© 2025 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

#### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: <a href="https://www.leviton.com/company/about-leviton/locations">www.leviton.com/company/about-leviton/locations</a>

## © 2025 Leviton Manufacturing Co., Inc.