

WORKER-X

WORKER-X

Upper: Action Leather 1.6-1.8mm

Lining: Sandwich Air Mesh

Outsole: new formula DESMA Machine Dual PU

Hydrolysis Resistant, Polyether-based PU soles

SRC Outsole Anti-slip

Electrical Hazard Resistant to 6KV by ASTM F2413-2018

Composite Plastic WIDE TOE by I/C 75 ASTM Impact Compression

Kevlar Midsole by ASTM PR ASTM Anti-Nail

100% Metal-Free Eyelet

Insole: EVA+Air Mesh 3mm thickness

Standard: ASTM Composite Plastic toe+Kevlar Midsole+EH6K+SRC



GENUINE

PERFORMANCE FOOTWEAR

Slip Resistant | Oil resistant | Dielectric Metal Free

Complies with the ASTM F2413-2018 Standard Test Methods, under test

Impact Resistance (I): ASTM F2412-18 (1/75) (101.7J)

Puncture Resistance (PR): ASTM F2412-18 (>1200N)

Wider Composite Toe, 200J Shock Resistant

Full Breathable Top Durable Leather and Lining Mesh

EURO SIZE	US SIZE	WIDTH
40	7 - 7.5	STANDARD
43	10 - 10.5	STANDARD
44	11 - 11.5	STANDARD

 SAFETY TOE CAP  ANTI-SLIP  SHOCK ABSORPTION  OIL RESISTANT  PETROL AND CHEMICAL RESISTANT  PR MIDSOLE

Manufacturer: LV International, Miami FL, 33166